

ACCESSORIES AND PARTS

SUBMERSIBLE ADAPTERS:

Coverts any MCM electrode for use underwater, includes your choice of a lead length (8', 25', 50', 100', 150' or 200') with banana plug. Water-tight connection. (* 8' model shown)



Cat. No.16305*

EXTENSIONS:

Intermediate electrode extension: 30" long. One or more can be used with MCM model IA and LC series meters or between the electrode and the standard electrode extension, so that the electrode can be easily placed at the desired location inside manholes, water tanks, etc. Will fit through 1" diameter augered hole.



Cat. No.16203

Electrode Extensions:

Electrode extensions 30" long. Side terminal connection allows use of the electrode without bending over or stooping. Extensions also available in 15" lengths.



Cat. No.16101

ANTI-FREEZE SOLUTION:

For use with any MCM electrode. Permits potential measurements with temperature as low as -10F (-23C) without danger of cracking electrode tube. Available in 8 oz. and 32 oz. (fl.) containers. Can be used year around.



Cat. No.17207

Cat. No.17105

COPPER SULPHATE:

Finely divided high-purity crystals. Available in ¾ lbs. and 2 ½ lbs. containers. Under normal conditions a ¾ lb. container will be sufficient to maintain one electrode for a year.



Cat. No.17003

Cat. No.16906

SPARE PLUG ASSEMBLY:

Replacement or spare plug assemblies are available for all electrodes and are supplied with an "O" ring gasket and protective cap. Note that the RE-5 and RE-5C plugs are interchangeable.



Cat. No.15403

Cat. No.15450

Cat. No.15607

Cat. No.15505

Cat. No. 17309